

SPECIFICATIONS OF FOG SEAL SPRAYER

FOG SEAL SPRAYER (FOR EMULSION / BITUMEN)

The Fog Seal Sprayer is mounted on rigid steel chassis and equipped with Bitumen Pump, Pump drive system and spray hose. The Fog Seal will be towed with the help of tow bar and it is provided 4 nos. scooter pneumatic tyres for easy mobility. The capacity of tank will be 200 litre. It is being used for filling cracks before pavements. It is useful for Bitumen & Emulsion Spray for tackcoat. Fire Tray is also provided for Bitumen heating purpose.

NO PRIME MOVER IS REQUIRED. MANUALLY OPERATED.



ISO : 9001
Certified Company

HIMAKSHI ROAD-CONS EQUIPMENTS PVT. LTD.

C-5, First Floor, Meghrath Building, Nr.Bank of Baroda,
Station Road, MEHSANA-384 001 (Gujarat) INDIA

Ph. : (91-02762) 256517, 243768

Fax : (91-02762) 254073, Cell : 9824039727

E-mail : himakshiroad@gmail.com

Visit us : www.himakshiroadequipments.com

Branch : 476-B, Model Town, Near Tejender Khurana Park, KARNAL-132 001 (Haryana). Ph. : (91-0184) 6522411 Fax : (91-0184) 2254786 Cell : 092159-01115