

SPECIFICATIONS

TRACTOR

NEW HOLLAND / MITSUBHISHI / MAHINDRA / SONALIKA OR OTHERS



SPREADING CAPACITY

2.5 Mtr to 4 Mtr

GLASS GRID LAYING SYSTEM

Glass Grid spool will hold in front of tractor by means of hydraulic cylinder and it will be layed / folded by means of front drive.



INITIAL COMPACTION

Glass Grid will be pressed by brush roller initially which are fitted in front of tractor after Glass Grid spool.



LIFTING & OTHER SYSTEM

All the systems are hydraulically operated such as lifting of spool, fitting of spool, dismantling of spool, laying of spool to ground. Hydraulic Cylinders are used & designed as per requirements.



COMPACTION

Compaction of Glass Grid will be done by brush roller, tractor wheels and rear wheels and additionally fitted solid wheels.



HIMAKSHI

ISO : 9001-2008
Certified Company

HIMAKSHI

ROAD-CONS EQUIPMENTS PVT. LTD.

C-5, First Floor, Meghrath Building, Nr.Bank of Baroda,
Station Road, MEHSANA-384 001 (Gujarat) INDIA

Ph. : (91-02762) 256517, 243768

Fax : (91-02762) 254073, Cell : 9824039727

E-mail : himakshiroad@gmail.com

Visit us : www.himakshiroadequipments.com

Branch : 476-B, Model Town, Near Tejender Khurana Park, KARNAL-132 001 (Haryana). Ph. : (91-0184) 6522411 Fax : (91-0184) 2254786 Cell : 092159-01115